

DOSAPLUS3 POLYPHOSPHATE DOSER WITH BYPASS

EAN	5027639902302
Product Code	902302
Pipe Diameter	1/2"
Body Material	Reinforced Polypropylene
Maximum Operating Pressure	8 bar (116 psi)
Maximum Operating Temperature	45°C (113°F)
Minimum Operating Temperature	4°C (39.2°F)
Total Maximum Hardness	300ppm
Average Flow Rate	1300 l/hour
Maximum Flow Rate	1800 l/hour
Width	65mm
Depth	126mm
Height	150mm



FOR DOMESTIC BOILERS UP TO 35kW



**SINGLE
APPLIANCE
PROTECTION**

TECHNICAL HELPLINE 01785 811636



360°

Cartridge Replacements in
Packs of 2 (Product Code 902319)
or
Packs of 12 (Product Code 902326).



THE DOSAPLUS PROPORTIONAL DOSING SYSTEM WITH POLYPHOSPHATE CHARGE READY CARTRIDGES IS IDEAL FOR ANTI-SCALE AND ANTI-CORROSION TREATMENT OF POTABLE WATER FOR HOME AND INDUSTRIAL USES.

Through the automatic and proportional dosing of the ready to use Poliphos, anti-scale and anti-corrosive product, the proportional dosing system DOSAPLUS3 releases polyphosphates that when dissolved in water have a conditioning effect on carbonates preventing them from depositing onto pipes and heaters.

Equipped with 360° rotational connection unit for easy connection to horizontal or vertical pipes.

All DosaPlus3 proportional dosing systems are equipped with a particular suction device that, through the Venturi effect, makes it possible to dose a quantity of polyphosphate within the limits established by standards for potable use into the flow.

Cartridge Replacements in Packs of 2 (Product Code 902319) or Packs of 12 (Product Code 902326).