

15mm SCALEMASTER MAGNETIC GOLD

EAN	5027639400143
Product Code	400143
Pipe Diameter	15mm
Body Material	Copper
Fitting Type	Compression
Maximum Flow Rate	32 litres / minute
Length	170mm
Diameter	35mm
Weight	.51kg
Guarantee	3 Years



**SINGLE
APPLIANCE
PROTECTION**



Features & Benefits

- Slip Couplings for easy fit
- Earth bonding not required
- Needs no chemicals or power
- Easily installed
- No moving parts, no maintenance required
- 3 Year product performance guarantee
- Manufactured in the UK
- Scalemaster patented technology
- WRAS Approved Product
- Single appliance protection
- Saves on energy costs

Installation Instructions

Magnetic Scale Inhibitors are only suitable for individual Appliance Protection.

- Plumb into the cold water supply pipe a minimum of one metre to a maximum of 2 metres before the appliance
- Operating temperature 4°C - 40°C
- Do not allow to freeze
- Maximum operating pressure 8 bar
- Do not solder
- Compression fitting torque setting 30 - 35 Nm
- Installation should be made to comply with all local byelaws and building regulations

Additional Information: Using a kettle - Magnetic effect changes hard water scale into tiny particles. The particles pass out of hot water heating systems in the flow of water called off for use. However to prevent an accumulation of scale particles in a kettle pour away any unused hot water and refill with cold.

22mm SCALEMASTER MAGNETIC GOLD

EAN	5027639400259
Product Code	400259
Pipe Diameter	22mm
Body Material	Copper
Fitting Type	Compression
Maximum Flow Rate	36 litres / minute
Length	165mm
Diameter	35mm
Weight	.51kg
Guarantee	3 Years



**SINGLE
APPLIANCE
PROTECTION**



Features & Benefits

- Slip Couplings for easy fit
- Earth bonding not required
- Needs no chemicals or power
- Easily installed
- No moving parts, no maintenance required
- 3 Year product performance guarantee
- Manufactured in the UK
- Scalemaster patented technology
- WRAS Approved Product
- Single appliance protection
- Saves on energy costs

Installation Instructions

Magnetic Scale Inhibitors are only suitable for individual Appliance Protection.

- Plumb into the cold water supply pipe a minimum of one metre to a maximum of 2 metres before the appliance
- Operating temperature - Cold water use only
- Do not allow to freeze
- Maximum operating pressure 8 bar
- Do not solder
- Compression fitting torque setting 50 Nm

Installation should be made to comply with all local byelaws and building regulations

Additional Information: Using a kettle - Magnetic effect changes hard water scale into tiny particles. The particles pass out of hot water heating systems in the flow of water called off for use. However to prevent an accumulation of scale particles in a kettle pour away any unused hot water and refill with cold.