

SCALEMASTER POWER CLEANER CONCENTRATE 250ml

EAN	5027639500492
Product Code	500492
Volume	250ml Bottle
Treats	100 litre (nom. 10 rad)
Minimum Dose Rate	0.25 v/v %
Colour Code	Purple
Leave in System (Min)	2 Hours
Leave in System (Max)	2 Weeks
Liquid Colour	Colourless to Slight Yellow
Box Quantity	20



POWER CLEANER - HEAVY DUTY CLEANER FOR POWERED FLUSHING OF SLUDGED HEATING SYSTEMS (including those with underfloor pipework and/or heat pumps). For the regeneration of established heating systems using powered flushing equipment. Assists in the rapid removal of iron oxide corrosion products (black magnetite and rust).

DOSE RATE: Bottle contains 250ml which is sufficient to treat 100 litres of system water. Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Scalemaster products.

APPLICATION: Dose via the vessel of a powered flushing unit, the feed and expansion tank, filling loop, magnetic filter or any convenient radiator. Circulate for at least 1 hour (hot where possible) then flush system (including each individual radiator where applicable) in accordance with BS 7593:2019. After cleaning, drain and thoroughly **flush out** through all drain points until water is clear to remove all contaminants. Heavily contaminated systems may require further treatment. At final fill add Scalemaster Inhibitor to prevent scale and corrosion.

HEALTH & SAFETY: Keep out of reach of children. Ensure there is sufficient ventilation of the area. If in contact with skin; wash immediately with plenty of soap and water. If in eyes; bathe the eye with running water for 15 minutes. If ingested; wash out mouth with water. If inhaled; consult a doctor if there are symptoms. Use protective gloves, clothing and eye protection. Ensure eye bath is to hand. Safety Data Sheet available on request. Do not use with PRIMATIC single-feed cylinders.'

STORAGE & DISPOSAL: Store in a cool, well-ventilated area. Keep container tightly closed. Do not allow to freeze. Dispose of contents and container in accordance with regional or national regulations. Product has no maximum shelf life when stored under normal conditions (4-40°C), however it is recommended that end users use the product within 6 months of purchase.