

Product Category: Chemicals

SM100C - CLEANSER CONCENTRATE



**TECHNICAL
HELPLINE**
01785 811636

EAN	5027639500928
Product Code	500928
Volume	250ml Bottle
Treats	100 litre (10 rad)
Colour Code	Blue
Leave in System (Min)	2 Hours
Leave in System (Max)	2 Weeks
Liquid Colour	Clear
Box Quantity	12
Shelf Life	Minimum 3 Years



SM100C - System Cleaner - FOR COMMISSIONING NEW CENTRAL HEATING SYSTEMS. Removes installation foulants, flux, grease and debris suspended in water by flushing. Should be left in system minimum 2 hours, maximum 2 weeks.

Dose Rate:

Bottle contains 250ml at double concentration. This treats up to a 100 litre (10 radiator). Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Instinct products.

Application:

Dose via the feed and expansion tank or via a radiator as per BS/7593:2006 at first fill. Run system on normal heating cycle. Leave in system minimum 2 hours, maximum 2 weeks. **Flush out** until water is clear to remove all contaminants.

Protection:

At final fill add Instinct SM100I Inhibitor to prevent scale and corrosion.

Health & Safety:

Keep out of reach of children. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. Do not use with PRIMATIC single feed cylinders.

Manufactured in the UK by Scalemaster® Limited.

All Scalemaster® Heating System Chemicals are manufactured using non-hazardous formulations.

Product Category: Chemicals

SM100C - CLEANSER CONCENTRATE

EAN	5027639500997
Product Code	500997
Volume	5 Litre Jerry Can
Treats	2000 litre
Colour Code	Blue
Leave in System (Min)	2 Hours
Leave in System (Max)	2 Weeks
Liquid Colour	Clear
Box Quantity	12
Shelf Life	Minimum 3 Years



SM100C - System Cleaner - FOR COMMISSIONING NEW CENTRAL HEATING SYSTEMS. Removes installation foulants, flux, grease and debris suspended in water by flushing. Should be left in system minimum 2 hours, maximum 2 weeks.

Dose Rate:

Bottle contains 5 Litres at double concentration. This treats up to a 2000 litre. Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Scalemaster products.

Application:

Dose via the feed and expansion tank or via a radiator as per BS/7593:2006 at first fill. Run system on normal heating cycle. Leave in system minimum 2 hours, maximum 2 weeks. **Flush out** until water is clear to remove all contaminants.

Protection:

At final fill add Instinct SM100I Inhibitor to prevent scale and corrosion.

Health & Safety:

Keep out of reach of children. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. Do not use with PRIMATIC single feed cylinders.

Manufactured in the UK by Scalemaster® Limited.

All Scalemaster® Heating System Chemicals are manufactured using non-hazardous formulations.