

Product Category: Water Softeners

SL (Soffline) 100 Electric Metered

EAN	5027639900216
Product code	900216
People	Up to 5
Height	545mm
Depth	460mm
Depth (With Connectors)	485mm
Width	275mm
Approximate regeneration time	42 Minutes
Resin volume	10 Litre
Salt used per regeneration	1500gm
Water used per regeneration	53 Litre
Average regeneration schedule	Every 3rd night
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Hi-Flo option	Yes
Power Source	240v 50hz mains transformer
Installation Orientation	Rear Only
Maximum Ambient Temperature	40°C
Maximum / Minimum Working Pressure	6 bar Max / 1 bar Minimum
Maximum Soft Water (at 200 ppm)	2500 Litres
Maximum Soft Water (at 300ppm)	1667 Litres
What salt to use	Granular or Tablet
Warranty	5 Years parts 2 Years Labour*



Requires one of the following installation kits

900803	15mm Standard Installation Kit
900858	22mm Hi-Flow Hoses x 2
900827	Combi installation Kit
900810	22mmHi-Flow Installation Kit

**TECHNICAL
HELPLINE
01785 811636**

* **IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.