

Product Category: Water Softeners

## SL (Soffline) 200 Plus Electric Metered

EAN	5027639900254
Product code	900254
People	Up to 7
Height	570mm
Depth	475mm
Depth (With Connectors)	500mm
Width	320mm
Approximate regeneration time	46 Minutes
Resin volume	15 Litre
Salt used per regeneration	2200gm
Water used per regeneration	59 Litre
Average regeneration schedule	Every 3rd night
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Hi-Flo option	Yes
Power Source	240v 50hz mains transformer
Installation Orientation	Rear Only
Maximum Ambient Temperature	40°C
Maximum / Minimum Working Pressure	6 bar Max / 1 bar Minimum
Maximum Soft Water (at 200 ppm)	3750 Litres
Maximum Soft Water (at 300ppm)	2500 Litres
What salt to use	Granular or Tablet
Warranty	5 Years parts 2 Years Labour*



### Requires one of the following installation kits

<b>900803</b>	15mm Standard Installation Kit
<b>900858</b>	22mm Hi-Flow Hoses x 2
<b>900827</b>	Combi installation Kit
<b>900810</b>	22mmHi-Flow Installation Kit

**TECHNICAL  
HELPLINE  
01785 811636**

\* **IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.